

you can  
**Canon**

LASERBASE

**Colour  
LaserBase MF8180C**

All-in-One colour laser printing,  
copying, faxing and scanning  
for small offices.



- Desktop Colour Laser All-in-One: print, fax, copy & scan
- Printing at 2400 x 600 dpi (enhanced)
- 19 ppm/cpm in mono, 4 ppm/cpm in colour with no warm-up time and fast first print out
- Colour scanning: 9600 x 9600 dpi enhanced
- Super G3 faxing, 256-page\* memory, Ultra High Quality imaging with 256 greyscales
- 50-page Automatic Document Feeder
- 250-sheet paper cassette, 125-sheet Multi-Purpose Tray
- Standard built-in Ethernet interface for network printing/faxing
- Easy to replace toner and drum cartridges
- Simple installation and small footprint

\*based on ITU-T Standard Chart No.1



**NETWORK PRINTING AND FAXING**  
A standard built-in Ethernet interface provides productive network printing and PC faxing for workgroups. It's ready to use and easy to install into your existing network. A Remote User Interface ensures simple control for users and network administrators

**ULTRA FAST PERFORMANCE**

Speed up your workflow with fast printing or copying at 19 pages per minute. Canon's Colour on demand fixing technology virtually eliminates warm-up time, resulting in rapid first prints - in approximately 22 seconds. The 128 MB printer memory accelerates image processing tasks. Plus a USB 2.0 Hi-Speed interface transfers data speedily between your LaserBase and PC.



**Specifications Colour LaserBase MF8180C**

<b>TYPE</b> Machine Type Available functions Paper scanning type	Colour laser flatbed All-in-One Colour print, colour scan, colour copy, fax, network ready Flatbed and Automatic Document Feeder
<b>PRINTER FUNCTIONS</b> Printing Method Print Speed Print resolution Enhanced resolution Printer Memory Consumables & yield (based on 5% coverage)  Smoothing (dpi) Paper capacity Cassette Multi-purpose tray Paper Size Toner saver mode	Colour laser beam printing 19 ppm mono / 4 ppm colour 600 x 600 dpi 2400 x 600 dpi 128MB Toner Cartridge 701 Black - 5000 pages Toner Cartridge 701L / 701 Cyan - resp. yield of 2000 & 4000 pages Toner Cartridge 701L / 701 Magenta - resp. yield of 2000 & 4000 pages Toner Cartridge 701L / 701 Yellow - resp. yield of 2000 & 4000 pages Drum Cartridge 701 - 20000 pages mono / 5000 pages colour 2400 x 600 dpi  250 sheets 125 sheets A4, LTR, LGL, Envelope (COM10, Monarch, DL, ISO-5) Yes (Mono printing only)
<b>FAX FUNCTION</b> Transmission speed Modem speed Compression method Fax resolution Image processing system Half-tone Automatic document feeder Memory transmission FAX memory Memory back up Dual access One touch dials Coded dials Group dial Redial FAX/TEL auto switch Answering machine hook up Remote reception Sequential broadcast Error correction mode(ECM) Memory reception Reports	Approx. 3 secs per page <sup>1</sup> Super G3 33.6Kbps MH, MR, MMR, JBIG Standard, Fine, Super Fine, Ultra Fine UHQ 256 grey scales 50 pages Yes 256 pages 1 hour Yes 18 100 117 Yes Yes Yes Yes Yes (max 119 destinations) Yes Yes One-Touch, Coded Dial, Group Dial, and User Data Lists. Activity, TX and RX Report
<b>SCANNER FUNCTIONS</b> Scanner type Automatic document feeder Scanner resolution Colour scanning depth Greyscale gradation Compatibility OCR bundle Other features	Colour flatbed CCD Yes 1200 x 2400 dpi (9600 x 9600 dpi enhanced) 48bit/24bit (in/Out) 8bit TWAIN, WIA Yes Scan to Email, Scan to PDF
<b>COPIER FUNCTIONS</b> Copy resolution Copy modes Copy speed	600 x 600 dpi Text, Photo, Text & Photo 19 cpm (Mono) 4 cpm (Colour)

Multiple copy Zoom ratio First copy output time(FCOT)  Other features	Up to 99 copies 50-200% approx. 22 secs (Mono) approx. 46 secs (Colour) Auto Exposure, Collate Copy, Reserve Copy
<b>PC INTERFACE &amp; SOFTWARE</b> Interface type Software Supported OS  Printer driver Scan driver Fax driver Scan to E mail Other features Bundled Software	USB 2.0 Hi-Speed Windows 98/Me/2000/XP/Server 2003 (network connection only) Yes Yes Yes (TX only) Yes Scan to PDF, Scan to OCR Presto!PageManager, ScanSoft OmniPage SE
<b>NETWORK FEATURES</b> Type Connection Type Network Protocols  Supported OS  Others	Ethernet (10BaseT/100BaseTX) RJ45 TCP/IP (DHCP, BOOTP, RARP, ICMP, DNS, Fixed Address, HTTP) Windows 98/Me/2000 Professional/2000 Server/XP/Server 2003 RUI (Remote User Interface)
<b>GENERAL FEATURES</b> Number of language (LCD message)  Dimensions without trays (W x D x H) with trays (W x D x H) Installation space including trays (WxD) Weight Power Source Consumption  Acoustic Noise Levels	15 (Czech, Danish, Dutch, English, Finnish, French, German, Hungarian, Italian, Norwegian, Portuguese, Russian, Slovenian, Spanish, Swedish)  510 x 512 x 588 mm 510 x 512 x 641 mm  510 x 916 mm approx. 36kg AC 200-240V, 50-60Hz Max: 1200W Standby: 35W Energy Save Mode: 8W Standby: 35dB(A) max Copy: under 54 dB(A) max
<b>SYSTEM REQUIREMENTS</b> Software Operating System	Minimum Requirements: IBM or IBM compatible PC, CD-ROM drive or network environment with the access to CD-ROM, USB port Windows 98: 90Mhz Pentium processor or higher/ at least 32 MB of RAM and 115MB of available HDD space. (only for ) Windows Me: 150Mhz Pentium processor or higher/ at least 32 MB of RAM and 115MB of available HDD space. Windows 2000 Professional: 133Mhz Pentium processor or higher/ at least 64 MB of RAM and 115MB of available HDD space. Windows XP: 300Mhz Pentium processor or higher/ at least 64 MB of RAM and 115MB of available HDD space. Windows Server 2003: 300Mhz Pentium processor or higher/ at least 64 MB of RAM and 115MB of available HDD space.
<p><sup>1</sup> Based on ITU-T Chart No.1. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. (TM) and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.</p>	



you can  
**Canon**

Canon Copiers  
3 The Forum  
Tring Technology Park  
Icknield Way  
Tring  
Hertfordshire HP23 4JX

www.canoncopiers.co.uk  
Tel:08000 822226  
Fax: 01442 828811  
Email: info@canoncopiers.co.uk

